



Filter Element: 63-762-40K

| Technical Specification | |
|----------------------------------|---|
| Description | Disposable Particulate Filter Element |
| Materials of Construction | Borosilicate Glass Microfibres bonded with Kynar fluorocarbon (P.V.D.F.) resin |
| Filtration Efficiency | Better than 99.9998+% removal of 0.1 micron particles and aerosols |
| Air Flow Resistance | Less than 6.0KPa at 6 m/min in air at 25°C |
| Dimensions | I.D. - 65.5mm ± 0.25mm O.D. - 75.5mm ± 1.5mm Length - 762.0mm ± 0.25mm |
| Strength (dry) | Burst minimum - 0.8 Bar Collapse minimum - 1.2 Bar |
| Temperature Resistance | -50°C to +150°C maximum in air |
| Chemical Resistance | Resistant to all mineral, vegetable and synthetic compressor lubricants. Consult chemical resistance chart for other gases and liquids. |

For further specific information please contact our Technical Department
This is a guide only

| | | | |
|---|---|--|--|
| Headline Filters Limited Mill Hall Business Estate Aylesford Kent, ME20 7JZ www.headlinefilters.com info@headlinefilters.com | Filter Element: 63-762-40K | | THE COPYRIGHT OF THIS DRAWING IS RESERVED BY HEADLINE FILTERS. IT IS ISSUED ON CONDITION THAT IT IS NOT COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY, OR IN PART WITHOUT CONSENT IN WRITING. |
| | Material: Borosilicate Glass Microfibres bonded with Kynar fluorocarbon (P.V.D.F.) resin | | |
| DO NOT SCALE DRAWING IF IN DOUBT ASK | | | |