



Headline Filters

Air Flow Rates for Aluminium Housings in Nm³/hr at 0.5 Bar Pressure Drop

Housing Model	Line Size	Element Grade	Air Line Pressure (Bar)								
			1	2	3	4	5	6	7	10	16
	½"	70C	12	21	28	37	44	50	58	79	22
315, 315A	or	50C	4	6	9	11	13	15	17	24	37
	¼"	CC	2	4	5	6	7	8	10	13	21
360, 360I,	¼"	70C	31	48	62	77	94	109	125	172	266
360FI, 360A,	or	50C	12	19	24	29	37	42	48	66	103
360AF	½"	CC	7	11	14	18	21	25	29	39	62
370, 370I,		70C	73	107	144	180	218	252	288	395	611
370FI, 370A,	½"	50C	29	43	58	72	87	101	115	158	244
370AF		CC	19	29	38	48	57	67	76	106	163
380AHP,	¾"	70C	191	286	380	478	574	672	764	1058	1628
		50C	50	71	96	120	144	168	193	264	407
380AFHP	or	CC	40	57	76	96	115	134	154	212	327
385AHP,		70C	383	571	760	957	1148	1344	1541	2115	3275
	1"	50C	83	126	166	210	251	294	335	465	717
385AFHP	1 ½"	CC	59	90	120	149	179	210	241	331	513
390AHP,		70C	676	1012	1340	1674	2018	2352	2693	3694	5717
		50C	168	252	334	423	505	588	677	924	1434
390AFHP	2"	CC	119	181	240	300	357	420	482	663	1027
		70C	1350	2025	2700	3375	4050	4725	5400	7425	11475
395A	3"	50C	390	585	780	975	1170	1365	1530	2145	3315
		CC	276	420	560	691	827	975	1089	1539	2374

- Notes:**
- (1) Airline pressures above 10 Bar apply only to housings with aluminium bowls.
 - (2) Housings with polycarbonate bowls are limited to 10 Bar.
 - (3) Auto float drains require minimum 1 Bar pressure to function correctly.



Headline Filters Limited
 Mill Hall Business Estate
 Aylesford
 Kent, ME20 7JZ
www.headlinefilters.com
info@headlinefilters.com
 Tel: 01622 718927
 Fax: 01622882448

