



HF Headline Filters

Filter Element: SS-25-64-100

Technical Specification	
Description	Stainless steel Filter Element
Materials of Construction	316 sintered stainless steel
Filtration Efficiency	100 Micron Nominal
Air Flow Resistance	16 KPa at 6 m/min in air at 25°C
Dimensions	I.D. - 26.00mm ± 0.25mm
	O.D. - 29.50mm ± 1.5mm
	Length - 61.00mm ± 0.25mm
Strength (dry)	Collapse minimum - 175 Bar
Temperature Resistance	-50°C to +480°C maximum in air
Chemical Resistance	Resistant to all mineral, vegetable
	And synthetic compressor lubricants.
	Consult chemical resistance chart for Other gases and liquids.



For further specific information please contact our Technical Department
This is a guide only

Headline Filters Limited Mill Hall Business Estate Aylesford Kent, ME20 7JZ www.headlinefilters.com info@headlinefilters.com	Filter Element: SS-25-64-100		THE COPYRIGHT OF THIS DRAWING IS RESERVED BY HEADLINE FILTERS. IT IS ISSUED ON CONDITION THAT IT IS NOT COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY, OR IN PART WITHOUT CONSENT IN WRITING.
	Material: 316 sintered stainless steel		
DO NOT SCALE DRAWING IF IN DOUBT ASK			