



**Filter Element: SS-51-230-25H**

Technical Specification	
<b>Description</b>	Stainless steel Filter Element
<b>Materials of Construction</b>	316 sintered stainless steel
<b>Seals</b>	h Te erature nneale o er
<b>Filtration Efficiency</b>	25 Micron Nominal
<b>Air Flow Resistance</b>	Less than 2.8 KPa at 6 m/min in air at 25°C
<b>Dimensions</b>	I.D. - 51.00mm ± 0.25mm
	O.D. - 56.00 ± 1.5mm
Finished Length with seals - 230.00 ± 0.25mm	
<b>Strength (dry)</b>	Collapse minimum - 175 Bar
<b>Temperature Resistance</b>	-50°C to +480°C maximum in air
<b>Chemical Resistance</b>	Resistant to all mineral, vegetable
	And synthetic compressor lubricants.
	Consult chemical resistance chart for
	Other gases and liquids.

For further specific information please contact our Technical Department  
This is a guide only

Headline Filters Limited Mill Hall Business Estate Aylesford Kent, ME20 7JZ www.headlinefilters.com info@headlinefilters.com	<b>Filter Element: SS-51-230-25H</b>		THE COPYRIGHT OF THIS DRAWING IS RESERVED BY HEADLINE FILTERS. IT IS ISSUED ON CONDITION THAT IT IS NOT COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY, OR IN PART WITHOUT CONSENT IN WRITING.
	<b>Material:</b> 316 sintered stainless steel		
<b>DO NOT SCALE DRAWING          IF IN DOUBT ASK</b>			